

# 修改/升级

目录 [\[Hide\]](#)

- 1. 描述
- 2. 参数
- 3. HTTP 方法
- 4. 测试 URL 请求范例
- 5. 返回值

## 描述 [Top](#)

修改/升级当前 Linux 分销主机订单

## 参数 [Top](#)

名称	数据类型	必填 / 可选	
auth-userid	<a href="#">整数</a>	必填	<a href="#">验证参数</a> <a href="#">代理商 ID</a>
api-key	<a href="#">字符串</a>	必填	<a href="#">验证参数</a> <a href="#">APIKEY</a>
order-id	<a href="#">整数</a>	必填	The Order ID which is to be modified..需要修改的订单 ID
new-plan-id	<a href="#">整数</a>	必填	需要升级/降级的套餐。获取套餐信息 i.e. plan-id etc，使用 <a href="#">这一方法</a>
months	<a href="#">整数</a>	必填	The number of months in the new plan for which the Order is to be modified.订单需要被修改至时间/月
invoice-option	<a href="#">字符串</a>	必填	<i>该参数决定了客户发票将如何处理。值可为: <code>NoInvoice</code>,<code>PayInvoice</code>, <code>KeepInvoice</code>, <code>OnlyAdd</code></i>

## HTTP 方法 [Top](#)

POST

## 测试 URL 请求范例 [Top](#)

### US Server

`https://test.httppapi.com/api/resellerhosting/linux/us/modify.json?auth-userid=0&api-key=key&order-id=0&new-plan-id=0&months=0&invoice-option=NoInvoice`

### UK Server

`https://test.httppapi.com/api/resellerhosting/linux/uk/modify.json?auth-userid=0&api-key=key&order-id=0&new-plan-id=0&months=0&invoice-option=NoInvoice`

### India Server

`https://test.httppapi.com/api/resellerhosting/linux/in/modify.json?auth-userid=0&api-key=key&order-id=0&new-plan-id=0&months=0&invoice-option=NoInvoice`

## 返回值 [Top](#)

返回值包含修改操作的执行信息